

Applications

Cement Australia's Jointfill Sand can be used with all types of paving and is suitable for areas with heavy traffic movement, high wind areas, driveways, pool surrounds and sloping sites. The product can be used to top up existing paving.

Features & Benefits

- Assist in maintain joint integrity and stability
- Locks pavers in to place
- Easy to use

Availability

Product available in 20kg bags

Things you might need

- Stiff broom
- Vibrating compactor

PRODUCT DATA SHEET Jointfill Sand

Cement Australia Jointfill Sand is a special blend of graded fine sands designed to help lock into place all types of brick and block paving.

Directions for Use

- 1. Lay pavers as per manufacturer's instructions
- 2. Jointfill Sand should be thoroughly swept into all joints using a stiff broom. Pavers should be dry to allow the free flow of the sand into the joints
- 3. When all joints are filled a vibrating compactor or similar equipment should be worked over the entire area of the paving to assist the flow of sand into the joints and ensure that the joints are firm
- 4. Thoroughly sweep the paved surface, topping up where necessary and remove all excess surface sand

Limitations

Jointfill Sand is not recommended for use in paving where gaps are greater than 3mm wide. Cement Australia's Sand and Cement, swept in dry or mixed wet, is recommended for paving with gaps wider than 3mm.

Storage, Handling & Safety

- Care should be taken when lifting bagged products as personal injury may occur. It is suggested that when lifting bagged materials, the load is shared with another person
- Jointfill Sand should be stored in a dry place, off the ground and be protected from the ingress of moisture

Further Hints & Tips

- One 20kg bag of Jointfill Sand covers approximately 3.5 m₂ at a 3mm gap (brick shaped pavers)
- One 20kg bag of Jointfill Sand covers approximately 12m² at a 3mm gap (400mm square pavers)

NOTE: The Jointfill Sand Safety Data Sheet (SDS) is available at www.cementaustralia.com.au

PRODUCT DISCLAIMER

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all implied warranties, conditions and guarantees imposed by legislation. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations or (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, to the extent permitted by law Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.

Cement Australia Pty Ltd ABN 75 104 053 474

18 Station Avenue, Darra QLD 4076

For more information call **1300 CEMENT** (1300 236 368) or visit **www.cementaustralia.com.au**

Mix it with the best.

