# SAFETY DATA SHEET Cement Grade Limestone

## Section 1: Identification of the Material and Supplier

### **Company Details**

### **Cement Australia Pty Limited**

ABN 75 104 053 474	
18 Station Avenue Darra, Queensland 4076	<b>Tel:</b> 1300 CEMENT (1300 236 368) <b>Fax:</b> 1800 CEMENT (1800 236 368) <b>Website:</b> www.cementaustralia.com.au
Emergency Contact Number:	<b>Contact Person:</b> Technical Manager Telephone: 1300 CEMENT (1300 236 368 - Business Hours) or Poisons Information Centre 13 11 26
Manufacturing Plants	
Gladstone: Railton:	Landing Rd, Fisherman's Landing, Gladstone QLD 4680 Cement Works Rd, Railton, TAS 7305

### Product

Name:	Limestone
Other Names:	Calcium Carbonate, Crushed limestone, Agricultural lime, Calcite
Use:	Portland Cement mineral addition, construction material, soil treatment, acid neutralisation, agricultural applications

## **Section 2: Hazards Identification**

Hazardous Substance. Non-dangerous Goods

### Carcinogenicity: Category 1 Specific Target Organ Toxicity (Repeated Exposure): Category 2

### Hazard statements

H350	May cause cancer by inhalation.
H373	May cause damage to organs through prolonged or repeated exposure.
Prevention statements	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P281	Use personal protective equipment as required.
Response statements	
P308 + P313	IF exposed or concerned: Get medical advice/ attention.

For more information call **1300 CEMENT** (1300 236 368) or visit **www.cementaustralia.com.au** 





DANGER

Storage statements	
P405	Store locked up.
Disposal statements	
P501	Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards No information provided.

## **Section 3: Composition/Information on Ingredients**

Chemical Entity	Formula	Conc.	CAS Number
Silica, Crystalline - Quartz	Si-O2	<10%	14808-60-7
Calcium Carbonate	Ca-C-O3	>60%	1317-65-3
Clay	Not Available	<10%	Not Available

### **Section 4: First Aid Measures**

Swallowed:	Rinse mouth and lips with water. Do not induce vomiting. Give 1 -2 large glasses of water or milk. Never give liquids to an unconscious person. Seek urgent medical attention.
Eyes:	Flush immediately with large amounts of water, lifting the lower and upper lids occasionally. Seek medical attention.
Skin:	Wash affected area thoroughly with soap and water. Seek medical aid.
Inhaled:	Remove from exposure. If breathing is difficult or has stopped, administer artificial respiration or oxygen as indicated. Immediately seek medical aid.
First Aid Facilities:	Eye wash station. Washing facilities with running water.

## **Section 5: Fire Fighting Measures**

Flash Point:	N/A
Hazchem Code:	None allocated
Flammable Limits:	N/A
Extinguishing Media:	Considered non-combustible. Use media appropriate for surrounding fire.
Hazards from Combustion Products:	None
Special Fire Fighting Procedures:	There are no unusual fire and explosion hazards. It has and is used to prevent explosions and fires in coal mines.
Unusual Fire and Explosion Hazards:	Not combustible. Excessive dust generation creates a potential explosion hazard.

### **Section 6: Accidental Release Measures**

Spills:If spilt (bulk), wear dust-proof goggles, PVC/rubber gloves and a Class P1 (Particulate) respirator.Absorb with moist sand or similar and place in sealable containers for disposal.

## Section 7: Handling and Storage

Handling:When supplied in bags these need to be handled in accordance with manual handling Code of Practice.Storage:Protect from moisture to prevent hardening. Storage of product may be in concrete silos, steel bins, or<br/>plastic lined multi-ply paper bags.



### **Section 8: Exposure Controls/Personal Protection**

### **Exposure standards**

No exposure standards have been entered for this product.

	·	т	WA	5	STEL
Ingredient	Reference	ppm	mg/m³	ppm	mg/m³
Aluminium & compounds	SWA [Proposed]		1		
Aluminium oxide	SWA [AUS]		10		
Calcium carbonate (Limestone, Marble)	SWA [AUS]		10		
Iron oxide fume (Fe <sub>2</sub> O <sub>3</sub> ) (as Fe)	SWA [AUS]		5		
Magnesite	SWA [AUS]		10		
Quartz (respirable dust)	SWA [AUS]		0.05		

**Biological limits** No biological limit values have been entered for this product.

### **Personal Protection**

Skin:	Clean, body-covering clothing should be worn to prevent irritation in situation where direct contact with product may occur or dust levels are excessive.
Eyes:	Employees should be required to wear chemical safety splash goggles in situations where direct contact with the product may result in eye injury.
Respiratory:	Appropriate respiration selection depends on the type and magnitude of exposure.

## **Section 9: Physical and Chemical Properties**

Crushed stone up to 40mm
No distinctive odour
Not applicable
2570°C CaO / 2800° F MgO
Not applicable
Not applicable
Not applicable
Not applicable
Negligible
Up to 40mm

## **Section 10: Stability and Reactivity**

Chemical Stability:	Chemically stable
Incompatibility:	Acids, Chlorinated Phenols + Potassium Nitrate, Moleic Anhydride, Nitroparaffins and Phosphorus
Hazardous Decomposition or By-Products:	None expected
Conditions to avoid:	Will not occur
Hazardous Polymerization:	N/A



## **Section 11: Toxicological Information**

### 11.1 Information on toxicological effects

Acute toxicity	This product is expected to be of low toxicity. Under normal conditions of use, adverse health effects are not anticipated. However, ingestion of large quantities may result in nausea, vomiting and gastrointestinal irritation.						
Ingredient	Oral LD50 Dermal LD50 Inhalation LC50						
Calcium Carbonate	> 2	2000 mg/kg (rat)	> 2000 mg/kg (rat)	> 3.0 mg/L			
Aluminium Oxide	> {	5000 mg/kg (rat)					
Skin Eye	Not classified as a skin irritant. Contact may result in mechanical irritation, redness and rash. Not classified as an eye irritant. However, this product may cause mechanical eye irritation with redness and lacrimation.						
Sensitisation	Not classified as causing skin or respiratory sensitisation.						
Mutagenicity	Insufficient data available to classify as a mutagen.						
Carcinogenicity	Crystalline silica is classified as carcinogenic to humans (IARC Group 1). However, there is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis.						
Reproductive	Insufficient data available to classify as a reproductive toxin.						
STOT - single exposure	Not classified as causing organ damage from single exposure.						
STOT - repeated exposure	Repeated exposure to respirable silica may result in pulmonary fibrosis (silicosis). Silicosis is a fibronodular lung disease caused by deposition in the lungs of fine respirable particles of crystalline silica. Principal symptoms of silicosis are coughing and breathlessness.						
Aspiration	This product is a solid and aspiration hazards are not expected to occur.						

## **Section 12: Ecological Information**

Ecotoxicity:	Product forms a weak alkaline slurry when mixed with water.
Persistence and Degradability:	Product is persistent and would have a low degradability.
Mobility:	A low mobility would be expected in a landfill situation.

## **Section 13: Disposal Considerations**

Limestone can be treated as a common waste for disposal or dumped into a landfill site in accordance with local authority guidelines.

Keep material out of storm water and sewer drains.

Measures should be taken to prevent dust generation during disposal, and exposure and personal precautions should be observed (see above).



## **Section 14: Transport Information**

UN Number:	None allocated
Proper Shipping Name:	None allocated
Class and Subsidiary Risk:	None allocated
Packing Group:	None allocated
Special precautions for user:	Avoid generating and breathing dust
Hazchem Code:	None allocated

### **Section 15: Regulatory Information**

15.1 Safety, health	, and environmental regulations/legislation specific for the substance or mixture
Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.
Inventory listings	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS or are exempt.

### **Section 16: Other Information**

For further information on this	Telephone: 1300 CEMENT (1300 236 368 - Business Hours)
product contact:	Facsimile: 1800 CEMENT (1800 236 368)

### Next Review Date for this MSDS: 31 December 2024.

### **Australian and New Zealand Standards:**

AS 2161: Industrial Safety Gloves and Mittens (excluding electrical and medical gloves). AS/NZ 1336: Recommended Practices for Occupational Eye Protection. AS/NZS 1715: Selection, use and maintenance of respiratory protective devices. AS/NZS 1716: Respiratory protective devices. AS/NZS 4501: Occupational protective clothing.

### **Advice Note:**

Cement Australia believes the information in this document to be accurate as at the date of preparation noted below, but, to the maximum extent permitted by law, Cement Australia accepts no responsibility for any loss or damage caused by any person acting or refraining from action because of this information.

The provision of this information should not be construed by anyone as a recommendation to use this product. In particular, no one should use any product in violation of any patent or other intellectual proprietary rights or in breach of any statute or regulation.

Users should rely on their own knowledge and inquiries and make their own determination as to the applicability of this information in relation to their particular purposes and specific circumstances. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace and in conjunction with other substances or products.

[End SDS]

