## **CLAY** FOR RENDERING & BRICKLAYING

**20** 

A plasticiser for cement rendering and plastering Improves workability of mortars and renders FIRECLAY – provides refractory properties





A plasticiser for render, brick and block laying

Improves workability for renders and mortars based on sands that are ' deficient in clay content

Provides refractory properties






cementaustralia.com.au or call 1300 CEMENT (1300 236 368)

with Confidence





FOR RENDERING

CLAY





Cement Australia Clay is a finely milled, air separated clay used as a plasticiser in mortar and render applications where sands are low in clay content.

- Clay can be used as a general purpose filler.
- Use as little Clay as possible to produce the required workability of the mortar or render.
- Cement Australia does not specify any mix designs incorporating Clay as the mix is dependent on the sands used and the sands can vary.
- It is advisable to trial Clay in the product formulation to ensure that the product performance is appropriate.
- ✓ Mortars complying to AS 3700 should be tested as described in the Standard if Clay is added to these mixes. This helps to ensure that the mix design conforms to the Standard with respect to performance and durability requirements.
- ✓ A test panel should be prepared before Clay is added to a mix especially where colour variation is a concern.

## **PRODUCT DISCLAIMER**

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all implied warranties, conditions and guarantees imposed by legislation. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations or (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, to the extent permitted by law Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.

## LIMITATIONS

Clay should not be considered to be a substitute for Hydrated Lime.

Mortars and renders containing excessive Clay may reduce bond, flexural and compressive strengths while contributing to higher shrinkage in the finished product.

To view all product limitations, storage & handling tips please visit **cementaustalia.com.au** 

Item Code 16456 Cement Australia Clay 20kg







## Safety Data Sheet available at cementaustralia.com.au