

PROSTRENGTH RAPID SET MORTAR

**HARDENS
IN 10 MINS**
further construction
can take place
after 1 hour



- ✓ **Easy to use** – for smaller jobs mix only enough material required directly in the bucket
- ✓ **Excellent bond to concrete and masonry**
- ✓ **1 bucket is enough to bed 1 standard toilet pan** - covers approximately 1m² at 2mm thick

Build with Confidence

cementaustralia.com.au or call **1300 CEMENT** (1300 236 368)

**CEMENT
AUSTRALIA®**



Suitable for around the home and building site, patching around electric and plumbing fittings, re-pointing on block, brick and rendered surfaces.

- ✓ A quality blend of cement, graded sand and specialty additives
- ✓ Excellent workability
- ✓ Just add water into the bucket and mix (no mess, no fuss)
- ✓ For fast repairs around the home and building sites
- ✓ Good for small jobs – convenient & easy to use
- ✓ Suitable for both internal and external use

Examples of Use:



Before: Drain Base Repair



After: Drain Base Repair



Before: Driveway Repair



After: Driveway Repair

The recommended shelf life of PROStrength Rapid Set Mortar is approximately 12 months from the date of manufacture when stored properly in a dry location, protected from moisture, out of direct sunlight, and in an undamaged package.

PRODUCT DISCLAIMER

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all implied warranties, conditions and guarantees imposed by legislation. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations or (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, to the extent permitted by law Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.



TOILET PAN BEDDING



PLUGGING & GROUTING



FIXING BRICKWORK

SUGGESTIONS FOR USE

Add water gradually (approx 1.4 litres per 8kg bucket / 175ml per 1kg of dry product) and blend thoroughly to achieve a workable mix. **Note:** Additional water may prolong setting and weaken the overall strength of the mortar.

IMPORTANT Ensure you are able to quickly transfer the blended mortar to the area you are applying it to, in order to avoid it setting in the mixing vessel. Product is expected to stiffen in 10 minutes, recommended to ensure product is placed within 5 minutes.

Ambient temperatures may prolong or shorten set times; product will work best in working conditions between 10°C and 32°C.

Apply the PROStrength Rapid Set Mortar as required to complete the task at hand.

Tips

- Clean all tools and equipment with water without delay after use.
- Hot temperatures will impact set times, avoid working in direct sunlight.
- For non-structural applications.

Item Code 17732

Cement Australia
PROStrength
Rapid Set Mortar 8kg



9 311808 177322

