

SAFETY DATA SHEET



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name AGGREGATES

Synonyms BALLAST • CAPPING • COARSE AGGREGATE • CRUSHER DUST • DRAINAGE AGGREGATE • FILL • GRAVEL • ROAD BASE

1.2 Uses and uses advised against

Uses INDUSTRIAL & COMMERCIAL APPLICATIONS

1.3 Details of the supplier of the product

Supplier name CEMENT AUSTRALIA PTY LIMITED

Address 18 Station Ave, Darra, QLD, 4076, AUSTRALIA

Telephone (07) 3335 3000; 1300 236 368

Fax (07) 3335 3000; 1800 236 368

Email ca.compliance@cemaust.com.au

Website <http://www.cementaustralia.com.au>

1.4 Emergency telephone numbers

Emergency (07) 3335 3000; 1300 236 368 (Business Hours)

Emergency 13 11 26 (After Hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Not classified as a Physical Hazard

Health Hazards

Carcinogenicity: Category 1A

Specific Target Organ Toxicity (Repeated Exposure): Category 2

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms



Hazard statements

H350i May cause cancer by inhalation.

H373 May cause damage to organs through prolonged or repeated exposure.

PRODUCT NAME **AGGREGATES**

Prevention statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P308 + P313	IF exposed or concerned: Get medical advice/ attention.
-------------	---

Storage statements

None allocated.

Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

2.3 Other hazards

The hazard information provided in this Safety Data Sheet applies to the dusts within Aggregates and particularly inhalable dust particles with a diameter less than 75 microns.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
AGGREGATE and DUST MAY CONTAIN >1% QUARTZ (CRYSTALLINE SILICA)	14808-60-7	238-878-4	<100%

Ingredient Notes Depending upon the source material, may contain varying amounts of respirable quartz (crystalline silica).

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water till dust removed. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	Due to product form and application, ingestion is considered unlikely.
First aid facilities	Eye wash facilities and safety shower are recommended.

4.2 Most important symptoms and effects, both acute and delayed

Chronic exposure to respirable crystalline silica may result in lung fibrosis (silicosis), and Chronic Obstructive Pulmonary Disease (COPD). Chronic exposure to non-Quartz mineral dusts may also result in COPD. Principal symptoms of silicosis and COPD are cough and breathlessness. Respirable Crystalline Silica (RCS) is classified as carcinogenic to humans (IARC Group 1).

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non-flammable.

5.3 Advice for firefighters

Non-flammable, treat surrounding fires as per their requirements.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

PRODUCT NAME AGGREGATES

6.1 Personal precautions, protective equipment and emergency procedures

If dust is or could be present, wear Personal Protective Equipment (PPE) as detailed in Section 8 of this SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for disposal. Avoid generating dust.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid eye or skin contact and inhalation.

7.2 Conditions for safe storage, including any incompatibilities

All stockpiles and dumps should be managed to avoid dust generation (highly recommended - moisture addition to surfaces, especially disturbed faces), run-off, or the risk of collapse.

7.3 Specific end uses

This product contains more than 1% crystalline silica and, therefore, is considered a Crystalline Silica Substance in accordance with the Safe Work Australia Model Code of Practice: Managing risks of respirable crystalline silica in the workplace. This product should be used in accordance with this Code of Practice and the requirements of the WHS Regulator.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Quartz (respirable dust)	SWA [AUS]	--	0.05	--	--
Quartz (respirable dust)	SWA [Proposed]	--	0.05	--	--

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls

All work should be carried out in such a way as to minimise dust generation (recommend dampening of material and stockpile surfaces), and eliminate lung exposure to dust. Dust suppression and/or extraction may be used, if necessary, to control airborne dust levels. Work areas should be cleaned regularly, especially prior to conducting maintenance activities. Maintain respirable dust and Quartz (Respirable Crystalline Silica) levels below the recommended exposure standards (see 8.1 above).

PRODUCT NAME AGGREGATES

PPE

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye / Face	Wear safety glasses or dust-proof goggles when handling material to avoid contact with eyes. Refer to AS/NZS 1336.
Hands	Where hands are subject to "dry skin" or "skin tears", wear PVC, rubber or cotton gloves. Refer to AS/NZS 2161.
Body	Wear long sleeved shirt and full-length trousers.
Respiratory	Personal respiratory protection may be required where dust is airborne. The type of respiratory protection required depends primarily on the concentration of the inhalable and respirable dust in the air, and the frequency and length of exposure time. A suitable P2 particulate respirator chosen and used in accordance with AS/NZS 1715 and AS/NZS 1716 may be sufficient for many situations, but where high levels of dust are encountered, more efficient cartridge-type or powered respirators or supplied-air helmets or suits may be necessary. Use only respirators that bear the Australian Standards mark and are fitted and maintained correctly. Dust control measures providing respiratory protection against crystalline silica dust will also minimise and control any exposure to Actinolite.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	SOLID (COLOUR, SHAPE AND TEXTURE DEPENDS ON SOURCE OF RAW MATERIAL)
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT RELEVANT
pH	NOT AVAILABLE
Vapour density	NOT RELEVANT
Relative density	NOT AVAILABLE
Solubility (water)	INSOLUBLE
Vapour pressure	NOT RELEVANT
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT RELEVANT
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT EXPLOSIVE
Oxidising properties	NON OXIDISING
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

This material is considered inert.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Avoid dust generation. Do not use compressed air to clean surfaces of dust. Use vacuum or wet methods.

10.5 Incompatible materials

Incompatible with strong acids (e.g. hydrochloric acid).

10.6 Hazardous decomposition products

This material will not decompose to form hazardous products.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	This product is expected to be of low acute toxicity. Under normal conditions of use, adverse health effects are not anticipated. Ingestion of large amounts may cause gastrointestinal disturbances.
Skin	Contact may result in mechanical irritation, redness, rash and dermatitis.
Eye	Contact may result in mechanical irritation, lacrimation and redness.
Sensitisation	Not classified as causing skin or respiratory sensitisation.
Mutagenicity	Insufficient data available to classify as a mutagen.
Carcinogenicity	This product contains crystalline silica which is classified as carcinogenic to humans (IARC Group 1). However, there is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis. Therefore, preventing the onset of silicosis will also reduce the cancer risk. There is also information that concludes the risk of lung disease in smokers is greatly increased when combined with dust exposures.
Reproductive	Insufficient data available to classify as a reproductive toxin.
STOT - single exposure	Not classified as causing organ damage from single exposure.
STOT - repeated exposure	Repeated exposure to respirable silica above the regulated exposure standard may result in pulmonary fibrosis (silicosis) and COPD. Silicosis is a fibronodular lung disease caused by deposition in the lungs of fine respirable particles of crystalline silica. Exposure to silica at levels that appear not to cause overt silicosis can cause chronic bronchitis and chronic obstructive airways disease.
Aspiration	This product is a solid and aspiration hazards are not expected to occur.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

The main component/s of this product are not anticipated to cause any adverse effects to the environment.

12.2 Persistence and degradability

Product is persistent and non-degradable.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate.

12.4 Mobility in soil

A low mobility would be expected in a landfill situation.

12.5 Other adverse effects

Avoid contamination of drains and waterways.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal	Ensure product is kept damp, or covered with moist soil to prevent dust generation and dispose of to approved Council Landfill. Contact the manufacturer/supplier for additional information.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

PRODUCT NAME AGGREGATES

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user**Hazchem code** None allocated.**Other information** Avoid contamination of drains and waterways. Minimise ambient dust generation. In transit, highly recommend the dampening of load surface and covering of load. Moisture content should be constrained in order to prevent leakage from tail gates.**15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).**Inventory listings** **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**
All components are listed on AIIC, or are exempt.**16. OTHER INFORMATION****Additional information** Cement Australia believes the information in this document to be accurate as at the date of preparation, but, to the maximum extent permitted by law, Cement Australia accepts no responsibility for any loss or damage caused by any person acting or refraining from action because of this information. The provision of this information should not be construed by anyone as a recommendation to use this product. No one should use any product in violation of any patent or other intellectual proprietary rights or in breach of any statute or regulation. Users should rely on their own knowledge and inquiries and make their own determination as to the applicability of this information in relation to their particular purposes and specific circumstances. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace and in conjunction with other substances or products.**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

